

**Le Velvet** truly lives up to its name. This velour fabric offers a wonderfully soft texture, enhancing its remarkable durability. Interacting with Le Velvet creates memorable experiences that linger long after the touch.

#### Article specification:

|               |                   |                         |                   |
|---------------|-------------------|-------------------------|-------------------|
| Roll length:  | ~40 m             | Width:                  | 142 cm +   - 2 cm |
| Usable width: | 142 cm +   - 2 cm | Weight m DIN EN 12127:  | 750 g +   - 5 %   |
| Thickness:    | 1.5 mm +   - 2 %  | Weight m² DIN EN 12127: | 530 g +   - 5 %   |

#### Composition:

|                                                                                  |                       |                |
|----------------------------------------------------------------------------------|-----------------------|----------------|
|  | Surface EU 1007 2011: | 100% polyester |
|  | Base EU 1007 2011:    | 100% polyester |

#### Product profile for upholstery fabrics in living areas | according to DIN EN 14465:2006

|                                                                                    |                                                                          |                          | category                |
|------------------------------------------------------------------------------------|--------------------------------------------------------------------------|--------------------------|-------------------------|
|    | Abrasion test (cycles)<br>EN ISO 12947-1,2                               | 50.000<br>(loss of pile) | >80.000<br>(Martindale) |
|    | Pilling test EN ISO 12945-2 (2.000 T)                                    | 5                        | A                       |
|    | Tensile strength EN ISO 13934-1<br>warp:<br>weft:                        | 570 N<br>430 N           | A<br>B                  |
|    | Tear growth resistance EN ISO 13937-3<br>warp:<br>weft:                  | 100 N<br>70 N            | A<br>A                  |
|   | Resistance seam slippage EN ISO 13936-2<br>warp:<br>weft:                | 2.0 mm<br>2.0 mm         | A<br>A                  |
|  | Fastness to rubbing dry EN ISO 105-X12<br>bright colors<br>dark colors   | 4-5<br>4-5               | A<br>A                  |
|  | Fastness to rubbing wet EN ISO 105-X12<br>bright colors:<br>dark colors: | 4-5<br>4                 | A<br>A                  |
|  | Fastness to light EN ISO 105-B02-2<br>bright colors:<br>dark colors:     | 5<br>4-5                 | B<br>B                  |
|  | Permissible color tolerance<br>DIN EN 20105-A02                          | min. grade 4             | passed                  |